



Chemical protection


# ULTRANEО 382

Frequent contact | ultra-comfort wear

## Maximum comfort and chemical protection



CHEMICAL PROTECTION  
**TYPE A**



### SPECIFIC ADVANTAGES



#### Thermal protection

- Added comfort and thermal insulation, due to the cotton-knit lining



#### Comfort

- Extremely supple, due to the unique Mapa multi-layer process



#### Productivity

- Embossed texture for better grip on wet objects



#### Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting



#### Additional benefits

- Available in vending machine packaging

### INDUSTRIES

- Automotive/mechanical industry
- Chemical industry
- Other industries

### APPLICATIONS

- Engine part assembly
- Surface treatment
- Chemical product blending
- Handling drums of chemical products
- Manipulating valves
- Laboratory tests
- Machine maintenance



Chemical protection

# ULTRANEО 382

Frequent contact | ultra-comfort wear

## LEGENDS

EN388	MECHANICAL HAZARDS
	PERFORMANCE LEVELS (X = NOT TESTED)
2 1 2 1 X	
0-4 0-5 0-4 0-4 A-F P	
	Impact protection (optional)
	Cut resistance according to ISO 13997
	Puncture resistance
	Tear resistance
	Blade cut resistance
	Abrasion resistance
EN407	THERMAL RISKS (HEAT AND FIRE)
	PERFORMANCE LEVELS (X = NOT TESTED)
X 1 X X X X	
0-4 0-4 0-4 0-4 0-4 0-4	
	Resistance to large quantities of molten metal
	Small splashes of molten metal
	Radiant heat resistant
	Convective heat resistance
	Contact heat resistance
	Limited flame spread
EN ISO 374-1	CHEMICAL RISKS
	A: Methanol
TYPE A	L: Sulphuric acid 96%
	M: Nitric acid 65%
	N: Acetic acid 99%
	S: Hydrofluoric acid 40%
	T: Formaldehyde 37%
EN ISO 374-5	MICRO-ORGANISMS
	Protection against bacteria and fungi

## PRODUCT DETAILS

Interior finish	Textile support Mapa Technology
Exterior finish	Embossed texture
Material	Polychloroprene
Cuff characteristic	Feston Cuff
Colour.s	Blue
Length (cm)	36
Thickness (mm)	0.95
European sizes	6 7 8 9 10
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	1.5E+11 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	5.2E+10 Ω

## LOGISTIC DETAILS

Packaging	12 pairs/bag 72 pairs/carton
-----------	---------------------------------

## LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/08/18/1646 updated 02-07/10/2021
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France